

WORLD INTELLECTUAL PROPERTY ORGANIZATION International Bureau



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

	A1	(43) International Publication Date: 29 September 1994 (29.09.94)
	IS93/027	DE, DK, ES, FR, GB, GR, IF, IT, LU, MC, NL, PT, SE)
(22) International Filing Date: 22 March 1993	(22.03.9)
(71) Applicant: E.I. DU PONT DE NEMOURS AND O	MAN N	Published
[US/US]; 1007 Market Street, Wilmington, DE 1	9898 (U	With international search report.
(72) Inventors: CHU, I-Cheng; 1090 Cedar Grove Road PA 19008 (US). FRYD, Michael; 50 East Map Moorestown, NJ 08057 (US). LYNCH, Laurie, Garrett Road, Lansdowne, PA 19050 (US).	le Avent	
(74) Agents: FRICKE, Hilmar, L. et al.; E.I. du Pont d and Company, Legal/Patent Records Center, 1(Street, Wilmington, DE 19898 (US).	e Nemou 07 Mark	
·		·
(54) Title: AQUEOUS GRAFT COPOLYMER PIGME		

(57) Abstract

A pigment dispersion useful for forming coating compositions containing dispersed pigment, an aqueous carrier and a graft copolymer dispersant; wherein the graft copolymer has a weight average molecular weight of about 5,000-100,000 and has a polymeric backbone and macromonomer side chains attached to the backbone wherein 1) the polymeric backbone is hydrophobic in comparison to the side chains and contains polymerized ethylenically unsaturated, hydrophobic monomers and up to 20 % by weight, based on the weight of the graft copolymer, of polymerized ethylenically unsaturated acid containing monomers; and 2) the side chains are hydrophilic actions are hydrophilic and contains and contains and contains are hydrophilic are described to the backbone at a single terminal point and contains and contains and contains are hydrophilic. attached to the backbone at a single terminal point and contain polymerized ethylenically unsaturated monomers and 2-100 % by weight, based on the weight of the graft copolymer, of polymerized ethylenically unsaturated acid containing monomers and have a weight average molecular weight of about 1,000-30,000 and wherein the acid groups of the graft copolymer are neutralized with an inorganic base or an amine. The graft copolymer and a process for making the graft copolymer also are disclosed.

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AT	Austria	GB	United Kingdom	MR	Mauritania
ΑÜ	Australia	GE	Georgia	MW	Malawi
BB	Barbados	GN	Guinea	NE	Niger
BE	Belgium	GR	Greece	NL	Netherlands
BF	Burkina Faso	HU	Hungary	NO	Norway
BG	Bulgaria	Œ	Ireland	NZ	New Zealand
BJ	Benin	<u> </u>	Italy	PL	Poland
BR	Brazil	ĴР	Japan	PT	
BY	Belarus	KE	Kenya	RO	Portugal Pomonio
CA	Canada	KG	Kyrgystan	RU	Romania
CF	Central African Republic	KP			Russian Federation
CG	Congo	D.F	Democratic People's Republic of Korea	SD	Sudan
CH	Switzerland	KR		SE	Sweden
CI	Côte d'Ivoire		Republic of Korea	SI	Slovenia
CM	Cameroon	KZ	Kazakhstan	SK	Slovakia
CN		LI	Liechtenstein	SN	Senegal
-	China	LK	Sri Lanka	TD	Chad
cs	Czechoslovakia	LU	Luxembourg	TG	Togo
CZ	Czech Republic	LV	Larvia	TJ	Tajikistan
DE	Germany	MC	Monaco	TT	Trinidad and Tobago
DK	Denmark	MD	Republic of Moldova	UA	Ukraine
ES	Spain	MG	Madagascar	US	United States of America
FI	Finland	ML	Mali	UZ	Uzbekistan
FR	Prance	MN	Mongolia	VN	Viet Nam
GA	Gabon		-	***	

25

30

49

1

TITLE -<u>AOUEOUS-GRAFT-COPOLYMER-PIGMENT-DISPERSANTS</u>-

BACKGROUND OF THE INVENTION

This invention is directed to pigment dispersions and in particular to pigment dispersions formulated with a graft copolymer having acid functionality.

Water dispersible polymers are well known in the art and have 10 been used to form waterbased coating compositions, pigment dispersions, adhesives and the like. Graft copolymers containing carboxyl groups and the preparation of these polymers is shown in Japanese Laid Open Patent Application (Kokai) No. 1-182304 dated July 20, 1989. This reference shows graft copolymers that have carboxyl groups based on acrylic and methacrylic 15 acid in their side chains that have hydrophilic properties and teaches the use tertiary alcohol-based ester units of acrylic or methacrylic acid to form a macromonomer which is used to form a graft copolymer and then is hydrolyzed to form carboxylic acid groups on the polymer. The process taught by the reference is an inefficient process which does not form pure graft copolymer but results in a mixture of graft copolymer and low 20 molecular weight components that are detrimental to pigment dispersions formed from the graft copolymer and finishes formed from such a composition.

Typical problems with water based coating compositions are as follows: the pigment dispersion used to form the composition often is not completely compatible with the film forming binder constituents of the composition; the polymeric dispersant does not uniformly disperse the pigments and the pigments flocculate or agglomerate; or the dispersant does not enter into the curing reaction and remains in the film as an unwanted component which later may leach out or cause deterioration of the resulting finish.

A polymeric dispersant is needed that will form an aqueous pigment dispersion that is stable and not flocculated or agglomerated, that is compatible with a variety of polymeric film forming binders conventionally

used in water based coating compositions and that will cure with the film to form a finish of automotive quality that does not deteriorate on weathering because of adverse properties caused by the presence of the polymeric dispersant.

5

15

20

25

30

35

SUMMARY OF THE INVENTION

A pigment dispersion useful for forming coating compositions containing dispersed pigment, an aqueous carrier and a graft copolymer dispersant;

- wherein the graft copolymer has a weight average molecular weight of about 5,000-100,000 and comprises a polymeric backbone and macromonomer side chains attached to the backbone wherein
 - (1) the polymeric backbone is hydrophobic in comparison to the side chains and contains polymerized ethylenically unsaturated hydrophobic monomers and up to 20% by weight, based on the weight of the graft copolymer, of polymerized ethylenically unsaturated acid containing monomers; and
 - (2) the sidechains are hydrophilic macromonomers that are attached to the backbone at a single terminal point and contain polymerized ethylenically unsaturated monomers and 2-100% by weight, based on the weight of the macromonomer, of polymerized ethylenically unsaturated acid containing monomers and have a weight average molecular weight of about 1,000-30,000 and

wherein the acid groups of the graft copolymer are neutralized with an inorganic base or an amine.

The graft copolymer and the process for making the graft copolymer are also part of this invention.

DETAILED DESCRIPTION OF THE INVENTION

The novel pigment dispersion is stable and in general is non-flocculated or agglomerated and is compatible with a variety of polymeric film forming binders that are conventionally used in waterborne coating compositions and in particular is compatible with acrylic polymers that are widely used in waterborne coatings. The graft copolymer dispersant upon

Į.

5

10

15

20

25

30

35

3

curing of the coating, generally reacts with other film forming components of the coating composition and becomes part of the film and does not cause deterioration-of-the-film-upon-weathering-as-may-occur-if-it-was-an unreacted component of the film. Also, the freeze-thaw stability of the pigment dispersion is improved. Because the graft copolymer is an excellent pigment dispersant, the ratio of copolymer to pigment is less than is used with conventional dispersants particularly with metal oxide pigments such as iron oxide, titanium dioxide, zinc oxide and the like. The use of less dispersant reduces water sensitivity of the resulting finish.

The novel graft copolymer prepared by the process set forth herein is efficiently prepared and 100% graft copolymer is formed and not a mixture of graft copolymer and low molecular weight backbone polymer and copolymerized macromonomer segments as has generally been the case with prior art process used for making graft copolymers.

The graft copolymer contains about 50-90% by weight of polymeric backbone and correspondingly about 10-50% by weight of sidechains. The graft copolymer has a weight average molecular weight of about 5,000-100,000 and preferably about 10,000-40,000. The side chains of the graft copolymer are formed from hydrophilic macromonomers that have a weight average molecular weight of about 1,000-30,000 and preferably 2,000-5,000 and contain about 2-100% by weight and preferably 20-50% by weight, based on the weight of the macromonomer, of polymerized ethylenically unsaturated acid monomers. These sidechains are hydrophilic and keep the dispersant and pigments uniformly dispersed in the pigment dispersion and in the resulting coating composition.

The backbone of the graft copolymer is hydrophobic relative to the sidechains and may contain up to 20% by weight, preferably 1-10% by weight, based on the weight of the graft copolymer, of polymerized ethylenically unsaturated acid monomers which are listed hereinafter. The backbone contains polymerized hydrophobic monomers such as alkyl methacrylates and acrylates, cycloaliphatic methacrylates and acrylates and aryl methacrylates and acrylates as are listed hereinafter and also may contain up to 30% by weight, based on the weight of the graft copolymer, of polymerized ethylenically unsaturated non-hydrophobic monomers which may contain functional groups. Examples of such monomers are hydroxy

5

10

15

20

25

30

4

ethyl acrylate, hydroxy ethyl methacrylate, t- butylamino ethyl methacrylate, diethyl amino ethyl acrylate, diethyl amino ethyl methacrylate, acrylamide, nitro phenol acrylate, nitro phenol methacrylate, phthalimido methyl acrylate, phthalimido methacrylate, acrylic acid, acryloamido propane sulfonic acid.

The backbone of the graft copolymer has an affinity for the surface of the pigment used in the dispersion and anchors the copolymer to the pigment and keeps the pigment dispersed and prevents the graft copolymer from returning to the aqueous phase. Reactive groups on the backbone can react with the pigment and form a bond with the pigment.

Molecular weights are determined by Gel Permeation Chromatography using polystyrene as a standard.

The macromonomer contains a single terminal ethylenically unsaturated group which is polymerized into the backbone of the graft copolymer and primarily contains polymerized monomers of methacrylic acid, its esters, nitriles, amides or mixtures of these monomers.

Typical alkyl methacrylates that can be used have 1-8 carbon atoms in the alkyl group and are for example methyl methacrylate, ethyl methacrylate, propyl methacrylate, isopropyl methacrylate, butyl methacrylate, pentyl methacrylate, hexyl methacrylate, 2-ethyl hexyl methacrylate and the like. Cycloaliphatic methacrylates also can be used such as trimethylcyclohexyl methacrylate, isobutylcyclohexyl methacrylate, and the like. Aryl methacrylates also can be used such as benzyl methacrylate. Other polymerizable monomers that can be used are styrene, alpha methyl stryrene, methacrylamide and methacrylonitrile. The above monomers can also be used in the backbone of the graft copolymer.

The macromonomer can contain 2-100% by weight, preferably about 20-50% by weight, based on the weight of the macromonomer, of polymerized ethylenically unsaturated acid. Methacrylic acid is preferred particularly if it is the sole constituent. Other acids that can be used are ethylenically unsaturated carboxylic acids such as acrylic acid, itaconic acid, maleic acid and the like. Ethylenically unsaturated sulfonic, sulfinic, phosphoric or phosphonic acid and esters thereof also can be used such as styrene sulfonic acid, acrylamido methyl propane sulfonic acid, vinyl

10

15

20

25

30

35

phosphonic acid and its esters and the like. The above acids also can be used in the backbone of the graft copolymer.

Up-to-40%-by-weight, based-on-the-weight-of-the macromonomer, of other polymerized ethylenically unsaturated monomers can be present in the macromonomer. Primarily alkyl acrylates having 1-12 carbons in the alkyl group can be used such as methyl acrylate, ethyl acrylate, propyl acrylate, isopropyl acrylate, butyl acrylate, pentyl acrylate, hexyl acrylate, 2-ethyl acrylate, nonyl acrylate, lauryl acrylate and the like can be used. Cycloaliphatic acrylates can be used such as trimethylcyclohexyl acrylate, t-butyl cyclohexyl acrylate and the like. Aryl acrylates such as benzyl acrylate also can be used. The above monomers also can be used in the backbone of the graft copolymer.

One preferred macromonomer contains about 50-80% by weight of polymerized methyl methacrylate and 20-50% by weight of polymerized methacrylic acid and has a weight average molecular weight of about 2,000-5,000.

To ensure that the resulting macromonomer only has one terminal ethylenically unsaturated group which will polymerize with the backbone monomers to form the graft copolymer, the macromonomer is polymerized by using a catalytic chain transfer agent that contains a Co⁺² group, i.e. a cobalt chain transfer agent. Typically, in the first step of the process for preparing the macromonomer, the monomers are blended with an inert organic solvent which is water miscible or water dispersible and a cobalt chain transfer agent and heated usually to the reflux temperature of the reaction mixture. In subsequent steps additional monomers and cobalt catalyst and conventional azo type polymerization catalyst such as 2,2'-azobis(2-methylbutanenitrile) and 2,2'-azobis(2,4'-dimethylpentanenitrile) 2,2'-azobis(2,4-dimethyl-4-methoxyvaleronitrile) are added and polymerization is continued until a macromonomer is formed of the desired molecular weight.

Preferred cobalt chain transfer agents or catalysts are described in US Patent 4,680,352 to Janowicz et al and US Patent 4,722,984 to Janowicz. Most preferred are pentacyanocobaltate (II), diaquabis(borondifluorodimethyl-glyoximato) cobaltate(II) and diaquabis(borondifluorophenylglyoximato) cobaltate (II). Typically these

5

10

15

20

25

30

6

chain transfer agents used at concentrations of about 5-1000 ppm based on the monomers used.

After the macromonomer is formed as described above, optionally solvent is stripped off and the backbone monomers are added to the macromonomer along with additional solvent and polymerization catalyst. Any of the aforementioned azo type catalyst can be used as can other suitable catalyst such as peroxides and hydroperoxides. Typical of such catalyst are di-tertiarybutyl peroxide, di-cumylperoxide, tertiaryamyl peroxide, cumenehydroperoxide, di(n-propyl) peroxydicarbonate, peresters such as amyl peroxyacetate and the like. Polymerization is continued usually at the reflux temperature of the reaction mixture until a graft copolymer is formed of the desired molecular weight.

Typical solvents that can be used to form the macromonomer or the graft copolymer are ketones such as methyl ethyl ketone, isobutyl ketone, ethyl amyl ketone, acetone, alcohols such as methanol, ethanol, isopropanol, esters such as ethyl acetate, glycols such as ethylene glycol, propylene glycol, ethers such as tetrahydrofuran, ethylene glycol mono butyl ether and the like.

After the graft copolymer is formed, it is neutralized with an amine or an inorganic base such as ammonium hydroxide or sodium hydroxide and then water is added to form a dispersion. Typical amines that can be used include amino methyl propanol, amino ethyl propanol, dimethyl ethanol amine, triethylamine and the like. One preferred amine is amino methyl propanol and the preferred inorganic base is ammonium hydroxide.

Particularly useful graft copolymers include the following: a graft copolymer having a backbone of polymerized methyl acrylate and butyl acrylate and side chains of a macromonomer having a weight average molecular weight of about 2,000-5,000 and containing about 50-80% by weight, based on the weight of the macromonomer, of polymerized methyl methacrylate and 20-50% by weight, based on the weight of the macromonomer, of polymerized methacrylic acid.

a graft copolymer having a backbone of polymerized methyl acrylate and butyl acrylate and acrylamido methyl propane sulfonic acid and side chains of the above macromonomer.

10

20

25

30

35

a graft copolymer having a backbone of polymerized methyl acrylate and butyl acrylate and acrylic acid and side chains of the above macromonomer.

a graft copolymer having a backbone of polymerized ethyl acrylate and side chains of the above macromonomer.

a graft copolymer having a backbone of polymerized ethyl acrylate and acrylic acid and side chains of the above macromonomer.

a graft copolymer having a backbone of polymerized ethyl acrylate, methyl acrylate and acrylic acid and side chains of the above macromonomer.

To form a pigment dispersion or a mill base, pigments are added to the aqueous graft copolymer dispersion and then the pigments are dispersed using conventional techniques such as high speed mixing, ball milling, sand grinding, attritor grinding or two or three roll milling.

The resulting pigment dispersion has a pigment to dispersant binder weight

The resulting pigment dispersion has a pigment to dispersant binder weight ratio of about 0.1/100 to 1500/100.

Any of the conventional pigments used in paints in particular waterborne paints can be used to form the pigment dispersion such as metallic oxides like titanium dioxide, iron oxides of various colors, zinc oxide, carbon black, filler pigments such as talc, china clay, barytes, carbonates, silicates and a wide variety of organic pigments such as quinacridones, phthalocyanines, perylenes, azo pigments, indanthrones, carbazoles such as carbozole violet, isoindolinones, isoindolones, thioindigo reds, benzimidazolinones, metallic flakes such aluminum flake pearlescent flakes and the like.

It may be desirable to add other optional ingredients to the pigment dispersion such as antioxidants, flow control agents, rheology control agents such as fumed silica, microgels UV stabilizers screeners, quenchers and absorbers.

Pigment dispersions of this invention can be added to a variety of waterborne coating compositions such as primer, primer surfacers, topcoats which may be monocoats or basecoats of a clear coat base coat finish. These compositions preferably have an acrylic polymer as the film forming constituent and may contain crosslinking agents such as blocked isocyanate, alkylated melamines, epoxy resins and the like. Other film

10

forming polymers can also be used such as acrylourethanes, polyesters and polyester urethanes, polyethers and polyether urethanes that are compatible with the pigment dispersion. It is desirable to have the film forming polymer of the coating composition be similar to the polymer of the pigment dispersion so that on curing the polymer of the pigment dispersion will cure with the coating polymer and become part of the film or coating.

The following examples illustrate the invention. All parts and percentages are on a weight basis unless otherwise indicated. Molecular weights are determined by Gel Permeation Chromatography using polystyrene as the standard and tetrahydrofuran as the carrier solvent.

EXAMPLE 1

A macromonomer was prepared by charging the following constituents into a 3 liter flask equipped with a thermometer, stirrer dropping funnels, reflux condenser and a means for maintaining a nitrogen blanket over the reactants:

		Parts by Weight
	Portion 1	
	Methyl methacrylate	91.50
20	Methacrylic acid	91.50
	Methyl ethyl ketone	180.50
	Portion 2	
	Diaquabis(borondifluorodiphenyl-glyoximato)	0.07
	cobalt(II), Co(DPG-BF2)	
25	2,2'-azobis(2-methylbutanenitrile)	0.50
	Methyl ethyl ketone	20.00
	Portion 3	
	Methyl methacrylate monomer	251.80
	Methacrylic acid monomer	205.90
30	Portion 4	
	Co(DPG-BF ₂)	0.07
	2,2'azobis(2-methylbutanenitrile)	3.00
	Methyl ethyl ketone	45.00

	Portion 5		
	2,2'azobis(2,4-dimethylpentanenitrile)		1.50
	—Co(DPG-BF2)———————		0:03
	Methyl ethyl ketone		75.00
5	Portion 6		
	2,2'azobis(2,4-dimethylpentanenitrile)		1.50
	Co(DPG-BF ₂)		0.04
	Methyl ethyl ketone		75.00
		Total	1042 00

The composition was heated to its reflux temperature in about 20 minutes. Portion 2 was added and the composition was held at its reflux temperature for 5 minutes. Portion 3 and 4 were added simultaneously while the reaction mixture was held at its reflux temperature. The addition of Portion 3 took 4 hours to complete and the addition of Portion 4 took 90 minutes to complete. When the addition of Portion 4 was completed, the gradual addition of Portion 5 was begun and took about 75 minutes while the reaction mixture was held at its reflux temperature. Portion 6 was added over a 75 minute period while maintaining the reaction mixture at its reflux temperature. Reflux was continued for an addition 15 minutes and the composition was cooled to room temperature.

The resulting macromonomer solution had a solids content of about 53%, contained 60% methyl methacrylate and 40% methacrylic acid and had a weight average molecular weight of about 2,558 and a number average molecular weight of about 1,482.

Solvent was stripped off in a vacuum oven to give 100% solids macromonomer which is used below to form the graft copolymer.

The following constituents were charged into a two liter flask equipped as above to form a graft copolymer solution:

		Parts by Weight
30	Portion 1	
	Macromonomer (prepared above)	169.6
	Butyl acrylate monomer	12.9
	Methyl acrylate monomer	12.9
	Isopropanol	340.0

10

	Portion 2		
	2,2'-azobis(2-methylbutanenitrile)		6.0
	Isopropanol		60.0
	Portion 3		
5	Butyl acrylate monomer		202.5
	Methyl acrylate monomer		202.5
	Portion 4		
	2,2'-azobis(2,4-dimethylpentanenitrile)		2.0
	Isopropanol		180.0
10		Total	1184.4

15

20

25

Portion 1 was heated to its reflux temperature over a period of about 20 minutes. Portion 2 was added and simultaneously Portions 3 and 4 were gradually added over about a 3 hour period while maintaining the resulting reaction mixture at its reflux temperature. The reaction mixture was held at its reflux temperature for about an additional 2 hours and then cooled to room temperature.

The resulting graft polymer solution had a solids content of about 49% by weight and had the following overall approximate composition 36% butyl acrylate, 36% methyl acrylate, 17% methyl methacrylate and 11% methacrylic acid and had a weight average molecular weight of about 13,000 and a number average molecular weight of about 4,000.

A neutralized graft copolymer solution was prepared. About 37.4 parts by weight of 2-amino-2-methyl-1-propanol in 200.0 parts by weight of isopropanol was added to about 600 parts by weight of the above graft copolymer solution over about 20 minutes with stirring at room temperature and stirring was continues for about 30 minutes.

A waterborne pigment dispersion was prepared by charging the following constituents into a 01 Attritor media mill:

		Parts by Weight
30	Neutralized graft copolymer solution	44.84
	(prepared above)	
	Deionized water	314.44
	Quinacridone magenta pigment (Hostaperm	15.72
	Pink E 13-7000 from Hoechst Celanese Corp)	

11

Hi-density ceramic 1.6-2.5 mm grinding
media (ER120A from Netsch)

850.00

-Total---1225:00

The above constituents were ground for 20 hours at 500 rpm.

A uniform, transparent, waterborne pigment dispersion was formed that was stable and deflocculated and had a pH of 7.9.

Another neutralized graft copolymer solution was prepared. About 500 parts by weight of the above graft copolymer solution was added to 23 parts by weight of ammonium hydroxide over about 20 minutes with

stirring at room temperature and stirring was continued for about 30 minutes.

A waterborne pigment dispersion was prepared by charging the following constituents into a 01 Attritor media mill:

		Parts by Weight
15	Neutralized graft copolymer solution	122.92
	(prepared above neutralized with ammonium hydroxic	de)
	Isopropanol	10.40
	Non-ionic surfactant (octyl phenol polyether alcohol)	6.40
	Deionized water	196.28
20	Blue pigment (Palomar blue pigment EB-8592 from Mobay)	64.00
	Hi-density ceramic 1.6-2.5 mm grinding media (ER120A from Netsch)	850.00
	Total	1250.00

The above constituents were ground for 22 hours at 500 rpm. A uniform, waterborne pigment dispersion was formed that was stable and defloculated and had a pH of 9.14.

EXAMPLE 2

The following constituents were charged into a one liter flask equipped as in Example 1 to form a graft copolymer solution:

		Parts by Weight
	Portion 1	· -
	Macromonomer (prepared in Example 1)	60.0
	Butyl acrylate monomer	19.2
35	Methyl acrylate monomer	19.2

12

	Acrylic acid monomer		1.6
	Isopropanol		190.0
	Portion 2		
	2,2'-azobis(2-methylbutanenitrile)		1.0
5	Isopropanol		10.0
	Portion 3		
	Acrylic acid monomer		14.3
	Butyl acrylate monomer		76.6
	Methyl acrylate monomer		76.6
10	Macromonomer (prepared in Example 1)		32.5
	Isopropanol		35.0
	Portion 4		
	2,2'-azobis(2,4-dimethylpentanenitrile)		2.5
	Isopropanol		50.0
15	Portion 5		
	2,2'-azobis(2,4-dimethylpentanenitrile)		1.0
	Isopropanol		10.0
		Total	599.5

Portion 1 was heated to its reflux temperature over a period of about 20 minutes. Portion 2 was added and simultaneously Portions 3 and 4 were gradually added over about a 3 hour period while maintaining the resulting reaction mixture at its reflux temperature. The reaction mixture was held at its reflux temperature for about an additional 2 hours. Portion 5 was added and the reaction mixture was held at its reflux temperature for an addition 2 hours and then cooled to room temperature.

The resulting graft polymer solution had a solids content of about 48% by weight and the graft copolymer had the following overall approximate composition 32% butyl acrylate, 32% methyl acrylate, 12% methacrylic acid, 18% methyl methacrylate and 5% acrylic acid and had a weight average molecular weight of about 15,000 and a number average molecular weight of about 4,000.

30

A neutralized graft copolymer solution was prepared. About 39 parts by weight of 2-amino-2-methyl-1-propanol was added to about 380 parts by weight of the above graft copolymer solution over about 20 minutes

with stirring at room temperature and stirring was continues for about 30 minutes.

A-waterborne-pigment-dispersion-was-prepared-by-chargingthe following constituents into a 01 Attritor media mill:

5			Parts by Weight
	Neutralized graft copolymer solution		7.98
	(prepared above)		
	Deionized water		307.02
	Transparent iron oxide pigment		35.00
10	(Trans-oxide red 30-1005 from Hilton Davis)		
	Hi-density ceramic 1.6-2.5 mm grinding		850.00
	media (ER120A from Netsch)		
	·	Total	1200.00

The above constituents were ground for 22 hours at 500 rpm.

A uniform, transparent, waterborne pigment dispersion was formed that was stable and defloculated and had a pH of 8.5.

EXAMPLE 3

The following constituents were charged into a one liter flask equipped as in Example 1 to form a graft copolymer solution:

20		Parts by Weight
	Portion 1	
	Macromonomer (prepared in Example 1)	92.5
	Butyl acrylate monomer	9.6
	Methyl acrylate monomer	9.6
25	Isopropanol	190.0
	2-acrylamido-2-methyl-1-propane sulfonic acid	3.2
	Deionized water	3.0
	Portion 2	
	2,2'-azobis(2,4-dimethylpentanenitrile)	1.2
30	Isopropanol	10.0
	Portion 3	
	Butyl acrylate monomer	86.2
	Methyl acrylate monomer	86.2
30	Portion 3 Butyl acrylate monomer	86.2

14

	Portion 4		
	2,2'-azobis(2,4-dimethylpentanenitrile)		3.0
	Isopropanol		30.0
	Portion 5		
5	2-acrylamido-2-methyl-1-propanesulfonic acid		12.7
	Deionized water		12.0
	Portion 6		
	2,2'-azobis(2,4-dimethylpentanenitrile)		1.0
	Isopropanol		10.0
10		Total	560.2

15

20

25

Portion 1 was heated to its reflux temperature over a period of about 20 minutes. Portion 2 was added and simultaneously Portions 3, 4 and 5 were gradually added over about a 3 hour period while maintaining the resulting reaction mixture at its reflux temperature. The reaction mixture was held at its reflux temperature for about an additional 2 hours. Portion 6 was added and the reaction mixture was held at its reflux temperature for an addition 2 hours and then cooled to room temperature.

The resulting graft polymer solution had a solids content of about 53% by weight and the graft copolymer had the following overall approximate composition 32% butyl acrylate, 32% methyl acrylate, 12% methacrylic acid, 18% methyl methacrylate and 5% 2-acrylamido-2-methyl-1-propane sulfonic acid and had a weight average molecular weight of about 14,000 and a number average molecular weight of about 4,600.

A neutralized graft copolymer solution was prepared. About 40 parts by weight of 2-amino-2-methyl-1-propanol was added to about 485 parts by weight of the above graft copolymer solution over about 20 minutes with stirring at room temperature and stirring was continues for about 30 minutes.

A waterborne black pigment dispersion was prepared by charging the following constituents into a 01 Attritor media mill:

	Parts by Weight
Neutralized graft copolymer solution	46.66
(prepared above)	
Deionized water	257.84

	Carbon black pigment		45.50
	(Raven 1170 powder from Columbian)		
	Fi-density-ceramic-1.6-2.5-mm-grinding		850:00
	media (ER120A from Netsch)		
5	T	Total	1200.00
	The above constituents were ground	for 20	hours at 500 rpm.
	A uniform, waterborne pigment dispersion was for	med th	at was stable and
	deflocculated and had a pH of 8.2.		
	A waterborne blue pigment dispersion	on was j	prepared by
10	charging the following constituents into a 01 Attrito	or medi	a mill:
		\mathbf{P}	arts by Weight
	Neutralized graft copolymer solution		53.16
	(prepared above)		
	Deionized water		261.84
15	Blue pigment (Palomar blue pigment EB-8592 from Mobay)		35.00
	Hi-density ceramic 1.6-2.5 mm grinding		850.00
	media (ER120A from Netsch)		
	T	otal	1200.00
20	The above constituents were ground	for 24 h	ours at 500 rpm.
	A uniform, waterborne pigment dispersion was form	med tha	it was stable and
	deflocculated and had a pH of 8.5.		
	A waterborne blue pigment II dispers	sion wa	s prepared by
	charging the following constituents into a 01 Attrito	or medi	a mill:
25	·	Pa	arts by Weight
	Neutralized graft copolymer solution		53.16
	(prepared above)		
	Deionized water		261.84
	Blue pigment (BT-788-D blue pigment		35.00
30	from Cookson)		
	Hi-density ceramic 1.6-2.5 mm grinding media (ER120A from Netsch)		850.00
	To	otal	1200.00

The above constituents were ground for 24 hours at 500 rpm. A uniform, waterborne pigment dispersion was formed that was stable and defloculated and had a pH of 8.4.

EXAMPLE 4

The following constituents were charged into a one liter flask equipped as in Example 1 to form a graft copolymer solution:

5

25

30

			Parts by Weight
	Portion 1		
	Macromonomer (prepared in Example 1)		84.8
10	Ethyl acrylate monomer		12.9
	Isopropanol		170.0
	Portion 2		
	2,2'-azobis(2-methylbutanenitrile)		3.0
	Isopropanol		30.0
15	Portion 3		
	Ethyl acrylate monomer		202.5
	Portion 4		
	2,2'-azobis(2,4-dimethylpentanenitrile)		1.0
	Isopropanol		90.0
20		Total	594.2

Portion 1 was heated to its reflux temperature over a period of about 20 minutes. Portion 2 was added and simultaneously Portions 3 and 4 were gradually added over about a 3 hour period while maintaining the resulting reaction mixture at its reflux temperature. The reaction mixture was held at its reflux temperature for about an additional 2 hours and then cooled to room temperature.

The resulting graft polymer solution had a solids content of about 51% by weight and the graft copolymer had the following overall approximate composition 72% ethyl acrylate, 11% methacrylic acid, and 17% methyl methacrylate and had a weight average molecular weight of about 12,000 and a number average molecular weight of about 4,900.

A neutralized graft copolymer solution was prepared. About 18.4 parts by weight of 2-amino-2-methyl-1-propanol in 100.0 parts by weight of isopropanol was added to about 300 parts by weight of the above graft

copolymer solution over about 20 minutes with stirring at room temperature and stirring was continues for about 30 minutes.

A waterborne magenta pigment dispersion was prepared by charging the following constituents into a 01 Attritor media mill:

5			Parts by Weight
	Neutralized graft copolymer solution		47.81
	(prepared above)		
	Deionized water		302.19
	Quinacridone magenta pigment		17.50
10	(Hostaperm Pink E Trans 01 13-7014 from		
	Hoechst Celanese)		
	Hi-density ceramic 1.6-2.5 mm grinding		850.00
	media (ER120A from Netsch)		
		Total	1217.50

The above constituents were ground for 20 hours at 500 rpm. A uniform, transparent, waterborne pigment dispersion was formed that was stable and defloculated and had a pH of 8.5.

EXAMPLE 5

The following constituents were charged into a one liter flask equipped as in Example 1 to form a graft copolymer solution:

		Parts by Weight
	Portion 1	
	Macromonomer (prepared in Example 1)	85.0
	Ethyl acrylate monomer	84.0
25	Acrylic acid monomer	6.0
	Deionized water	40.0
	Isopropanol	90.0
	Portion 2	
	T-butyl perxoy pivalate (75% solids in	2.0
30	mineral spirits)	
	Isopropanol	20.0
	Portion 3	
	Acrylic acid monomer	24.0
	Ethyl acrylate monomer	366.0
35	Isopropanol	60.0

18

Portion 4		
T-butyl perxoy pivalate (75% solids in		4.0
mineral spirits)		
Isopropanol		180.0
•	Total	961 N

D------ 4

5

10

15

20

25

Portion 1 was heated to its reflux temperature over a period of about 20 minutes. Portion 2 was added and simultaneously Portions 3 and 4 were gradually added over about a 3 hour period while maintaining the resulting reaction mixture at its reflux temperature. The reaction mixture was held at its reflux temperature for about an additional hour and then cooled to room temperature.

The resulting graft polymer solution had a solids content of about 56% by weight and the graft copolymer had the following overall approximate composition 80% ethyl acrylate, 6% methacrylic acid, 9% methyl methacrylate and 5% acrylic acid and had a weight average molecular weight of about 24,000 and a number average molecular weight of about 5,300.

A neutralized graft copolymer solution was prepared. About 15.2 parts by weight of 2-amino-2-methyl-1-propanol in 100.0 parts by weight of isopropanol was added to about 200 parts by weight of the above graft copolymer solution over about 20 minutes with stirring at room temperature and stirring was continues for about 30 minutes.

A waterborne transparent iron oxide pigment dispersion was prepared by charging the following constituents into a 01 Attritor media mill:

			Parts by Weight
	Neutralized graft copolymer solution		63.60
	(prepared above)		
	Deionized water		240.90
30	Transparent iron oxide pigment		45.50
	(Sicotrans Red L 2817 from BASF)		
	Hi-density ceramic 1.6-2.5 mm grinding		850.00
	media (ER120A from Netsch)		
		Total	1200.00

35

The above constituents were ground for 20 hours at 500 rpm. A uniform, transparent, waterborne pigment dispersion was formed that was stable and deflocculated and had a pH of 8.2.

EXAMPLE 6

The following constituents were charged into a five liter flask equipped as in Example 1 to form a graft copolymer solution:

	•		Parts by Weight
	Portion 1		
	Macromonomer (prepared in Example 1)	•	255.0
10	Ethyl acrylate monomer		126.0
	Methyl acrylate monomer		126.0
	Acrylic acid monomer		18.0
	Isopropanol		1450.0
	Portion 2		
15	2,2'-azobis(2,4'dimethylpentanenitrile)		4.5
	Isopropanol		60.0
	Portion 3		
	Acrylic acid monomer		72.0
	Butyl acrylate monomer		549.0
20	Methyl acrylate monomer		549.0
	Portion 4		
	2,2'-azobis(2,4-dimethylpentanenitrile)		15.0
	Isopropanol		150.0
	Portion 5		
25	2,2'-azobis(2,4-dimethylpentanenitrile)		1.0
	Isopropanol		10.0
		Total	3385.5

Portion 1 was heated to its reflux temperature over a period of about 20 minutes. Portion 2 was added and simultaneously Portions 3 and 4 were gradually added over about a 3 hour period while maintaining the resulting reaction mixture at its reflux temperature. The reaction mixture was held at its reflux temperature for about an additional 2 hours and Portion 5 was added over a 5 minute period and reflux was continue for about 15 minutes then the resulting polymer solution was cooled to room temperature.

The resulting graft polymer solution had a solids content of about 50% by weight and the graft copolymer had the following overall approximate composition 40% butyl acrylate, 40% methyl acrylate, 6% methacrylic acid, 9% methyl methacrylate and 5% acrylic acid and had a weight average molecular weight of about 10,000 and a number average molecular weight of about 3,200.

A neutralized graft copolymer solution was prepared. About 130.0 parts by weight of 2-amino-2-methyl-1-propanol was added to about 2000 parts by weight of the above graft copolymer solution over about 20 minutes with stirring at room temperature and stirring was continues for about 30 minutes.

A waterborne white pigment dispersion was prepared by charging the following constituents into a 1-S Attritor media mill:

10

25

30

35

			Parts by Weight
15	Neutralized graft copolymer solution		712.80
	(prepared above)		
	Deionized water		1813.20
	Titanium dioxide pigment		3462.00
	2-amino-2-methyl-1-propanol		6.00
20	Hi-density ceramic 1.6-2.5 mm grinding		5600.00
	media (ER120A from Netsch)		
		Total	11594.00

The above constituents were ground for 3 hours at 500 rpm. A uniform, opaque, waterborne pigment dispersion was formed that was stable and loosely flocculated and had a pH of 8.6.

EXAMPLE 7

A white paint was prepared with the white pigment dispersion of Example 6 and was tinted with the black pigment dispersion of Example 2. The following constituents were blended together to form the white paint:

	Parts by Weight
Latex 1 (core shell microgel acrylic latex having a low	330.00
acid functionality)	
Latex 2 (core shell microgel acrylic latex having a high	330.00
acid functionality)	

	Deionized water	70.00			
	Ethylene glycol monobutyl ether	100.00			
	Crosslinking agent (monomeric hexa methyoxy methyl	54.00			
	melamine formaldehyde)				
5	Deionized Water	140.00			
	White pigment dispersion (prepared in	280.00			
	Example 6)				
	UV Screener ("Tinuvin" 1139 in water ethylene glycol	6.00			
	monobutyl ether and anionic surfactant)				
10	Acrysol ASE-60 Thickener (aqueous dispersion of	164.09			
	3.35% by weight of crosslinked acrylic emulsion polymer	·)			
	Demineralized water	97.50			
	Acrylsol ASE-60 Thickener	188.49			
	2-methyl-2-amino-1-propanol	3.50			
15	Total	1763.48			
The resulting basecoat had a pH of 7.4 and a H					
	viscosity at 5rpm using a #3 spindle of 2100 cps and 9.46% pigment				
	(titanium dioxide).	- -			
	FINE - 6-11 - 1 - 1 - 1 - 1				

The following amount of black waterborne dispersion of Example 2 was added to the white basecoat and evaluated for tinting strength.

		Parts by Weight
White basecoat (prepared above)		99.27
Black pigment dispersion (prepared in Ex.2)		0.73
	Total	100.00

The resulting composition had a tint strength of black/white of 1/100 and had an L Flat of 60.71 which is comparable or better than conventional commercial black pigment dispersions that are used to form coatings.

CLAIMS

1. A pigment dispersion comprising dispersed pigment, an aqueous carrier and a graft copolymer dispersant; wherein the graft copolymer comprises a polymeric backbone and macromonomer side chains attached to the backbone and has a weight average molecular weight of about 5,000-100,000 and wherein

5

10

15

20

35

- (1) the polymeric backbone is hydrophobic in comparison to the side chains and consists essentially of polymerized ethylenically unsaturated hydrophobic monomers and up to 20% by weight, based on the weight of the graft copolymer, of polymerized ethylenically unsaturated acid containing monomers; and
- (2) the sidechains are hydrophyilic macromonomers attached to the backbone at a single terminal point and consists essentially of polymerized ethylenically unsaturated monomers and 2-100% by weight, based on the weight of the macromonomer, of polymerized ethylenically unsaturated acid containing monomers and have a weight average molecular weight of about 1,000-30,000 and

wherein the acid groups of the graft copolymer are neutralized with an inorganic base or an amine.

- 2. The pigment dispersion of claim 1 in which the graft copolymer comprises about 10-50% by weight of macromonomer and correspondingly about 90-50% by weight polymeric backbone.
- 3. The pigment dispersion of claim 2 in which the macromonomer is formed by polymerizing the monomers in the presence of a catalytic chain transfer agent containing Co⁺².
 - 4. The pigment dispersion of claim 3 in which the macromonomer consists essentially of polymerized alkyl methacrylate monomers or any mixtures thereof each having 1-8 carbon atoms in the alkyl groups and 20-50% by weight, based on the weight of the macromonomer of

25

30

35

polymerized ethylenically unsaturated carboxylic acid and has a weight average molecular weight of about 2,000-5,000.

- 5. The pigment dispersion of claim 4 in which the macromonomer consists of 50-80% by weight of polymerized methyl methacrylate and 20-50% by weight of polymerized methacrylic acid.
- 6. The pigment dispersion of claim 3 in which the macromonomer consist essentially of polymerized alkyl methacrylate, having 1-8 carbon atoms in the alkyl groups and polymerized ethylenically unsaturated sulfonic acid and has a weight average molecular weight of about 2,000-5,000.
- 7. The pigment dispersion of claim 3 in which the backbone of the graft copolymer consist essentially of polymerized monomers of alkyl methacrylate, an alkyl acrylate or mixtures thereof where the alkyl groups have 1-8 carbon atoms and 1-10% by weight, based on the weight of the graft copolymer of polymerized ethylenically unsaturated carboxylic acid or ethylenically unsaturated sulfonic acid.
- 8. The pigment dispersion of claim 3 in which the backbone of the graft copolymer consist essentially of polymerized monomers of alkyl methacrylate, an alkyl acrylate or mixtures thereof where the alkyl groups have 1-8 carbon atoms and 1-10% by weight, based on the weight of the graft copolymer of polymerized methacrylic acid or acrylic acid.
 - 9. The pigment dispersion of claim 4 in which the macromonomer consists of 50-80% by weight of polymerized methyl methacrylate and 20-50% by weight of polymerized methacrylic acid and has a weight average molecular weight of about 2,000-5,000 and the backbone of the graft copolymer consists of polymerized methyl acrylate and butyl acrylate and the graft copolymer is neutralized with amino methyl propanol.
 - 10. The pigment dispersion of claim 4 in which the macromonomer consists of 50-80% by weight of polymerized methyl methacrylate and 20-50% by weight of polymerized methacrylic acid and has

24

a weight average molecular weight of about 2,000-5,000 and the backbone of the graft copolymer consists of polymerized methyl acrylate and butyl acrylate and acrylamido methyl propane sulfonic acid and the graft copolymer is neutralized with amino methyl propanol.

5

10

15

20

- 11. A graft copolymer comprising a polymeric backbone and macromonomer side chains attached to the backbone and has a weight average molecular weight of about 5,000-100,000 and wherein
 - the polymeric backbone is hydrophobic in comparison to the (1) side chains and consists essentially of polymerized ethylenically unsaturated hydrophobic monomers and up to 20% by weight, based on the weight of the graft copolymer, of polymerized ethylenically unsaturated acid containing monomers: and
 - **(2)** the sidechains are hydrophyilic macromonomers attached to the backbone at a single terminal point and consists essentially of polymerize ethylenically unsaturated monomers and 2-100% by weight, based on the weight of the macromonomer, of polymerized ethylenically unsaturated acid and are polymerized by using a catalytic chain transfer agent containing Co⁺² and the macromonomers have a weight

average molecular weight of about 1,000-30,000

- 12. The graft copolymer of claim 11 which comprises about 10-25 50% by weight of macromonomer and correspondingly about 90-50% by weight polymeric backbone.
- 13. The graft copolymer of claim 12 in which the macromonomer consists essentially of polymerized alkyl methacrylate monomers or any mixtures thereof each having 1-8 carbon atoms in the alkyl 30 groups and 20-50% by weight, based on the weight of the macromonomer, of polymerized ethylenically unsaturated carboxylic acid and has a weight average molecular weight of about 2,000-5,000.

20

- 14. The graft copolymer of claim 13 in which the macromonomer consists of 50-80% by weight of polymerized methyl methacrylate-and-20-50% by weight of polymerized-methacrylic-acid-
- 15. The graft copolymer of claim 12 in which the macromonomer consist essentially of polymerized alkyl methacrylate, having 1-8 carbon atoms in the alkyl group and polymerized ethylenically unsaturated sulfonic acid and has an weight average molecular weight of about 2,000-5,000.
- 16. The graft copolymer of claim 12 in which the backbone of the graft copolymer consist essentially of polymerized monomers of alkyl methacrylate, an alkyl acrylate or mixtures thereof where the alkyl groups have 1-8 carbon atoms and 1-10% by weight, based on the weight of the graft copolymer of methacrylic acid or acrylic acid.
 - 17. The graft copolymer claim 12 in which the backbone of the graft copolymer consist essentially of polymerized monomers of alkyl methacrylate, an alkyl acrylate or mixtures thereof where the alkyl groups have 1-8 carbon atoms and 1-10% by weight, based on the weight of the graft copolymer of ethylenically unsaturated sulfonic acid.
- 18. The graft copolymer of claim 12 in which the macromonomer consists of 50-80% by weight of polymerized methyl methacrylate and 20-50% by weight of polymerized methacrylic acid and has a weight average molecular weight of about 2,000-5,000 and the backbone of the graft copolymer consists of polymerized methyl acrylate and butyl acrylate.
- 19. The graft copolymer of claim 12 in which the macromonomer consists of 50-80% by weight of polymerized methyl methacrylate and 20-50% by weight of polymerized methacrylic acid and has a weight average molecular weight of about 2,000-5,000 and the backbone of the graft copolymer consists of polymerized methyl acrylate and butyl acrylate and acrylamido methyl propane sulfonic acid.



INTERNATIONAL SEARCH REPORT

Interna l Application No PCT/US 93/02701

			PC1/03 93	702701		
A. CLASSI IPC 5	FICATION OF SUBJECT MATTER C08F299/00 C09D17/00					
Accepting to	o International Patent Classification (IPC) or to both national classi	fication and IPC				
B. FIELDS	SEARCHED					
Minimum d IPC 5	ocumentation searched (classification system followed by classificat COSF COSD	tion symbols)				
Documentar	tion searched other than minimum documentation to the extent that	such documents are inc	luded in the fields s	earched		
Electronic data base consulted during the international search (name of data base and, where practical, search terms used)						
	IENTS CONSIDERED TO BE RELEVANT					
Category *	Citation of document, with indication, where appropriate, of the n	elevant passages		Relevant to claim No.		
x	EP,A,O 498 914 (E. I. DU PONT DE 19 August 1992 see the whole document	NEMOURS)		11-19		
A	EP,A,O 251 553 (E. I. DU PONT DE 7 January 1988	NEMOURS)		11-19		
A	EP,A,O 357 036 (MITSUBISHI RAYON) 1990) 7 March		11-19		
Α .	EP,A,O 248 574 (SOKEN KAGAKU) 9 [1987 see example 1	December		11-19		
A	EP,A,O 058 865 (BAYER) 1 September	er 1982	3	1		
Furt	her documents are listed in the continuation of box C.	X Patent family	members are listed	in annex.		
* Special categories of cited documents: T later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the						
'E' earlier document but published on or after the international filing date invention 'X' document of particular relevance; the cannot be considered novel or cannot			be considered to			
"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified) "O" document referring to an oral disclosure, use, exhibition or document is combined with one or more of the combined with one or the combined with o			claimed invention ventive step when the			
other means "P" document published prior to the international filing date but later than the priority date claimed "A" document member of the same patent						
Date of the actual completion of the international search Date of mailing of the international search		the international se	arch report			
9 December 1993 2 2. 12. 93						
Name and mailing address of the ISA Authorized officer						
	European Patent Office, P.B. 5818 Patentiaan 2 NL - 2280 HV Rijawijk Tel. (+ 31-70) 340-2040, Tx. 31 651 epo nl,					
	Fax: (+31-70) 340-2040, 1x. 31 631 epo ni,	Andrio	11o, G			



incormation on patent family members

Interna I Application No PCT/US 93/02701

Patent document cited in search report	Publication date	Patent family member(s)		Publication date
EP-A-0498914	19-08-92	US-A- AU-B- AU-A-	5010140 627419 7112791	23-04-91 20-08-92 20-08-92
EP-A-0251553	07-01-88	US-A- ——AU=B-	4746714 597534	24-05-88 31-05-90
		AU-A- CA-A- DE-A- JP-A-	7442087 1276332 3772652 62297306	24-12-87 13-11-90 10-10-91 24-12-87
EP-A-0357036	07-03-90	JP-A- JP-A- US-A- US-A-	2067303 2069503 5053461 5116910	07-03-90 08-03-90 01-10-91 26-05-92
EP-A-0248574	09-12-87	JP-A- DE-A- US-A- US-A-	62277408 3777692 4952638 5231141	02-12-87 30-04-92 28-08-90 27-07-93
EP-A-0058865	01-09-82	DE-A-	3106357	09-09-82

THIS PAGE BLANK (USPTO)